



Freemed™ platforms

Baropodometric platforms are developed to detect patients' pressure loads, in order to assess their posture, both in static and dynamic situations. They're made of aluminium, they're light-weight and can be transported up to the Dynamic version.



CERTIFICATIONS



www.sensormedica.com
info@sensormedica.com



Freemed™ platforms

TECHNICAL FEATURES

PHYSICAL DATA

- **BASE** | Dimensions: 440x620 mm; Thickness: 8 mm; Weight: 4 Kg
- **MAXI** | Dimensions: 640x740 mm; Thickness: 8 mm; Weight: 4 Kg
- **DYNAMIC** | Dimensions: 1240x740 mm; Thickness: 8 mm; Weight: 8,5 Kg
- **PROFESSIONAL** | Dimensions: 1840x740 mm; Thickness: 8 mm; Weight: 16Kg
- **EXTREME** | Dimensions: 2440x740 mm; Thickness: 8 mm; Weight: 22 Kg
- **SPORT** | Dimensions: 3040x740 mm; Thickness: 8 mm; Weight: 30 Kg

ELECTRICAL DATA

- Power supply: 15 Vcc
- Current consumption: from 50 mA to 450 mA

TECHNICAL FEATURES

- Types of sensors: resistive, gold-coated 24 k with conductive rubber
- Number of sensors: 10.000 m²
- Working temperature: 0-55° C
- Maximum pressure: 150 N/ cm²
- Acquisition frequency: up to 400 hz
- Life cycle: 1.000.000 cycles

CONNECTIVITY

They connect to the PC via USB cable 2.0. Also available in the Wi_Feet version, via Bluetooth connection.

SOFTWARE

All acquired data are processed by the FreeStep software, which offers detailed assessments and reports:

- Static acquisition
- Dynamic acquisition
- Stabilometric acquisition

CONFIGURATIONS

- BASE 40x40
- MAXI 60x50
- DYNAMIC 120x50
- PROFESSIONAL 180x50
- EXTREME 240x50
- SPORT 300x50

